Interior Showers - Elegance

Water saving rose allows temporary shut off - mix temperature and conserve water

Only suitable for pressure systems up to 45psi /3 bar

Compact design - for straight forward installation where space is limited

Standard connections - ½" hose connections, also suitable for Whale Quick Connect 15mm plumbing

Easy to use

controls

COMPLETE YOUR SYSTEM


Freshwater system accessories such as water filters, and pipework connections – page 76-77

YOU MAY ALSO LIKE

Whale Twist® - Deck Shower with integrated Temperature and Flow Controls – page 72 Watermaster Automatic Pressure Pumps – page 54 Whale chromed brass Faucets and showers – page 70-71

Accessories	
Product Code	Model
RT1770	Shower Riser Bar (for use with RT2498)
RT1270	Shower Wall Bracket (for use with RT2498)
RT9000	Replacement Microswitch Kit

Combination Faucet + Shower



 $5 \, {}^{9/_{16}}$ " retractable hose for neat installation

Extra long 1.7 m /

1 Year Warranty

Lightweight and Durable ABS showers

Marine grade materials Ideal for tight spaces

Robust ABS Construction

- Design for use with all types of galley pumps
- Connects to 3/8" or 1/2" hose connections
- Choice of single or mixer faucets
- Over 30 years experience designed, refined and made in our UK facility since the early 1980s



Model Specifications

Model	RT2498
Description	Mixer Combination Faucet / Shower
Colour	White
Hose Connections	1/2" Threaded
Base Plate (mm)	171 x 62 (6 ¾" x 2 ¼ε")
Depth Beneath Surface	80 mm (3 ½")
Connection to Quick Connect 15 mm Plumbing	WX1532
Connection to 13 mm $(1/2)$ Flexible Hose	WX1532 WX1584B
Service Kits	AS5133 - Replacement Handset ¹ / ² " BSP Threaded (white) AS5146 - Replacement Hose Assembly 1.7 m (5 ⁹ /16 ft) Long (white)

Note: These specifications are retail items only. For details of our bulk pack range for boat builders and wholesalers - contact Whale Support. 12mm faucets are now replaced by ½" connections models see table. AS5123 - handset 12mm, AS5145 12mm connection shower hose available.